



Pipe Coupling model: METAL LOCK

1. Available in S or L, short or long versions
2. Axially restrained pipe coupling - Pull Out Resistant
3. Prevents pipe connections from being pushed or pulled with grip rings and teeth locking the pipes in place together with the tightening of the bolt mechanism and solid bars.
4. Good for connecting Metal pipe
5. 316 Stainless Steel Coupling with EPDM, NBR, VITON or GORE-TEX seal



Higher Bar pressure available

OD	Pipe OD Range	Short length	Long Length	Pipe Gap (R) Short	Pipe Gap (R) Long	Maximum Bolt Tightness	Pressure	Estimated weight
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	Bar	(Kg)
21.3	21-23	57	72	5	10	15	32	0.35
26.7	26-28	57	72	5	10	15	32	0.4
33.4	33-34	57	100	5	10	15	32	0.45
42.2	40-44	57	100	5	10	15	32	0.5
48.3	46-50	57	100	5	10	15	32	0.55
60.3	58-62	80	139	5	10	30	32	1.2
73.0	71-75	80	139	10	30	30	32	1.3
88.9	88-92	107	203	10	30	50	28	2.7
114.3	112-116	107	203	10	30	50	28	3.4
141.3	139-143	116	203	10	30	80	28	4.8
168.3	166-170	116	203	10	30	80	24	5.8
219.1	217-221	155	255	10	30	100	16	8.7
273.0	271-275	155	255	10	30	100	16	10.7
323.9	321-325	155	255	10	30	100	14	14.9
355.6	353-357	155	255	10	30	100	14	15.2
406.4	404-408	155	255	10	30	120	12	17.6
457.2	455-459	155	255	10	30	120	12	18.2
508.0	506-510	155	255	10	30	120	10	21.5

Any OD size can be manufactured up to 508.0mm

