


Pipe Coupling model: OPEN FLEX 200-L

1. 200mm Long - 2 piece casing opening pipe clamp, with 6 x bolts
2. Non-axially restrained Pipe Coupling, and can also be used as a Pipe Repair Clamp.
3. Allows a 60mm pipe gap with a stainless steel strip insert fitted.
4. Allows slight misalignment, vibration in the pipeline and slight flex movement
5. Good for connecting Metal, PE, FRP, GRP, PVC pipe
6. 316 Stainless Steel Coupling with EPDM, NBR, VITON or SILICONE seal



Features: 12mm OD range in all sizes
only available in OPEN FLEX 200-L model

OD	Pipe OD Range	Length	Pipe Gap R	Maximum Bolt Tightness	Pressure
(mm)	(mm)	(mm)	(mm)	(Nm)	Bar
154.0	148 - 160	200	60	60	25
168.3	162-174	200	60	60	25
180.0	174-186	200	60	80	25
219.1	213-225	200	60	80	20
273.0	267-279	200	60	100	20
323.9	317-329	200	60	100	16
355.6	349-361	200	60	100	16
406.4	400-412	200	60	100	12
457.2	451-463	200	60	100	12
508.0	502-514	200	60	120	12
558.8	552-564	200	60	120	8
609.6	603-615	200	60	120	8
711.2	705-717	200	60	150	6
762.0	756-768	200	60	150	6
812.8	806-818	200	60	150	6
914.4	908-920	200	60	150	4
1016	1010-1022	200	60	150	4
1117.6	1111-1123	200	60	150	4

Any OD size can be manufactured
between 154.0mm - 2010.0mm

www.orbitcouplings.com.au

