


Pipe Coupling model: OPEN FLEX 300-L

1. 300mm Long - 2 piece casing opening pipe clamp, with 6 x bolts
2. Non-axially restrained Pipe Coupling, and can also be used as a Pipe Repair Clamp.
3. Allows a 120mm pipe gap with a stainless steel strip insert fitted.
4. Allows slight misalignment, vibration in the pipeline and slight flex movement
5. Good for connecting Metal, PE, FRP, GRP, PVC pipe
6. 316 Stainless Steel Coupling with EPDM, NBR, VITON or SILICONE seal



Higher Bar pressures available

OD	Pipe OD Range	Length	Pipe Gap R	Maximum Bolt Tightness	Pressure
(mm)	(mm)	(mm)	(mm)	(Nm)	Bar
219.1	217-221	300	120	100	20
273.0	271-275	300	120	100	20
323.9	320-327	300	120	100	18
355.6	352-359	300	120	100	18
406.4	403-409	300	120	100	14
457.2	454-460	300	120	100	14
508.0	505-512	300	120	100	14
558.8	555-562	300	120	100	12
609.6	606-613	300	120	100	12
711.2	707-715	300	120	100	10
762.0	758-766	300	120	100	10
812.8	809 - 817	300	120	100	10
914.4	910 - 918	300	120	100	10
1016	1012 -1020	300	120	100	10

Any OD size can be manufactured between 200.0mm - 1016.0mm

www.orbitcouplings.com.au

