




Pipe Coupling model: OPEN FLEX 400-L

1. 400mm Long - 2 piece casing opening pipe clamp, with 8 x bolts
2. Non-axially restrained Pipe Coupling, and can also be used as a Pipe Repair Clamp.
3. Allows a 200mm pipe gap with a stainless steel strip insert fitted.
4. Allows slight misalignment, vibration in the pipeline and slight flex movement
5. Good for connecting Metal, PE, FRP, GRP, PVC pipe
6. 316 Stainless Steel Coupling with EPDM, NBR, VITON or SILICONE seal



Higher Bar pressures available

OD	Pipe OD Range	Length	Pipe Gap R	Maximum Bolt Tightness	Pressure
(mm)	(mm)	(mm)	(mm)	(Nm)	Bar
219.1	217-221	400	200	100	20
273.0	271-275	400	200	100	20
323.9	320-327	400	200	100	18
355.6	352-359	400	200	100	18
406.4	403-409	400	200	100	14
457.2	454-460	400	200	100	14
508.0	505-512	400	200	100	14
558.8	555-562	400	200	100	12
609.6	606-613	400	200	100	12
711.2	707-715	400	200	100	10
762.0	758-766	400	200	100	10
812.8	809 - 817	400	200	100	10
914.4	910 - 918	400	200	100	10
1016	1012 -1020	400	200	100	10
1117.6	1113-1122	400	200	100	10
1219.2	1215-1224	400	200	100	8
1422.4	1418-1427	400	200	100	7
1524.0	1519-1529	400	200	100	5

Any OD size can be manufactured
between 200.0mm - 1524.0mm



www.orbitcouplings.com.au